

PMP 1240



PMP 1240

## Industrial Pressure Transmitter

- Accuracy:  $\pm 0.25\%$
- NACE compatible
- Low cost
- Class I, Div 1 intrinsically safe
- Class I, Div 1 explosionproof



The PMP 1240 industrial pressure transmitter has been designed for use with aggressive pressure media found in many industrial and process applications.

The fully welded 316L stainless steel pressure module ensures excellent media compatibility without compromising performance of Druck's micromachined silicon pressure sensing element.

The PMP 1240 incorporates developments from aerospace applications and high volume manufacturing advances to achieve excellent performance at competitive pricing. Industry demands for rapid delivery are met by holding fully compensated semi-finished stock of the most common ranges.

The integral low power, 3-wire, 1-5Vdc electronics provides power supply regulation, reverse polarity, overvoltage and EMC protection.

The PMP 1240 is intrinsically safe and explosionproof certified, thus making it suitable for use in the oil and gas industry.

This transmitter features a compact, rugged design with field proven electronics to ensure long term reliable measurement at an economical price.

## STANDARD SPECIFICATION

Operating Pressure Ranges  
0 to 2.5, 5, 10 psig;  
0-15, 30, 50, 60, 100, 150, 200, 300, 500,  
600, 750 psig or psia;  
0 to 1000, 1500, 2000, 3000, 5000, 7500,  
10,000, 15,000 psi sg or psia;

*Please refer to manufacturer for additional ranges.*

*Venting is provided by a flame arresting filter designed to allow the transmitter to breathe while preventing the ingress of fluids.*

Overpressure  
The rated pressure can be exceeded by the following without degrading performance:  
4X for ranges to 900 psig  
2X for ranges 1000 to 10,000 psi sg  
1.5X for range 15,000 psi

Pressure Containment  
6X full scale for vented gauge  
2500 psi for all absolute and sealed gauge ranges 2000 psi and below 20,000 psi for all absolute and sealed gauge ranges above 2000 psi

Pressure Media  
Fluids compatible with 316L stainless steel and Hastelloy C276 (NACE compatible)

Supply Voltage  
8-30 Vdc

Current  
< 2mA

Output Voltage  
1-5 Vdc  
Consult factory for availability of 4-20mA (PTX 1240)

Zero and Span Offset  
±0.5% full scale

Long term Stability  
±0.2% full scale per annum

Combined Non-linearity, Hysteresis and Repeatability  
±0.25% full scale BSL maximum

Temperature Limits  
Process: -40° to +250°F  
Storage: -50° to +185°F  
Compensated: -4° to +176°F

Operating Temperature Range  
-40° to +185°F

Temperature Effects  
±2% FS typically, ±3% FS maximum  
Thermal Error Band over compensated temperature range

Weight  
10 oz. nominal

Pressure Connection  
1/4" NPT female ranges up to 10,000 psi  
3/8" Autoclave for 15,000 psi range

Electrical Connection  
1/2" NPT male conduit fitting with 3 feet of cable (18 awg conductors)  
*Additional cable available upon request*

Ingress Protection  
Designed to meet Nema 4X when properly installed with conduit fitting connection

Voltage Spike Protection  
Units will withstand 600V spike test to ENV 50142 without damage applied between excitation lines and case

Safety Classifications  
UL intrinsically safe for  
Class I, Div 1, Grps A, B, C, D;  
Class II, Grps E, F, G

cUL intrinsically safe for  
Class I, Div 1, Grps A, B, C, D;  
Class II, Grps E, F, G

Factory Mutual Approvals  
Intrinsically safe for  
Class I, Div 1, Grps A, B, C, D;  
Class I, Div 2, Grps A, B, C, D;  
Class II, Grps E, F, G;  
Class III for hazardous locations

Explosionproof for  
Class I, Div 1, Grps A, B, C, D;  
Class I, Div 2, Grps A, B, C, D;  
Class II, Grps E, F, G;  
Class III for hazardous locations

Canadian Standards Association (CSA) Approvals  
Intrinsically safe in hazardous locations as designed by Class I, Div 1, Grps A, B, C, D; Class I, Div 2, Grps A, B, C, D; Class II, Grps E, F, G; Class III

Explosionproof in hazardous locations as designed by  
Class I, Div 1, Grps A, B, C, D;  
Class I, Div 2, Grps A, B, C, D;  
Class II, Grps E, F, G;  
Class III

## OPTIONS

Pressure port:  
1/2" NPT female via adapter  
1/4" NPT male via adapter  
1/2" NPT male, welded adapter  
Conduit fitting:  
1/2" NPT female, via adapter  
CSA/FM/UL Approval (state which logo on transducer)  
Extra cable length (state length in feet or meters)  
NIST Room Temperature 9-pt Calibration Certificate  
Alternate engineering units (equivalent to standard psi ranges)

## ORDERING INFORMATION

Please state the following:  
(1) Type number  
(2) Pressure range  
(3) Cable length  
(4) Options

## RELATED PRODUCTS

PTX 1240 2 wire, 4-20mA  
PTX 1230 Submersible  
MDK-24 Lightning Arrestor  
DPI 610 Portable Calibrators  
DPI 280 Indicator Series



*Please refer to the manufacturer for further information and data sheets.*

*Continuing development sometimes necessitates specification changes without notice.*

*Druck is an ISO 9001 registered company.*



## INSTALLATION DRAWINGS: Dimensions in inches/(mm)



**Druck**

Druck Incorporated  
4 Dunham Drive  
New Fairfield, CT 06812

**GE Druck 1240, PMP 1240**

**Distributor: ThermX Southwest 800-284-3769**

[www.thermx.com](http://www.thermx.com)

PDS-A075 4/00